



# FTC 120

## Cooled Incubator

Designed for BOD incubation



# High efficiency with A+ energy rate

- Usable volume 109 L
- Uniform temperature by the use of forced ventilation ( $\pm 0,5^{\circ}\text{C}$ )
- Constant temperature  $20^{\circ}\text{C}$
- Cooling system in A+ class energy rate
- Internal sockets to power devices
- 2-digit display of internal temperature
- Accepts 3 BOD Sensor System 6, or 2 BOD Sensor System 10
- Accepts 3 RESPIROMETRIC Sensor System 6



## INSTRUMENT - CODE

FTC 120

230V/50-60Hz

F10300305



## TECHNICAL DATA

DIGITAL DISPLAY	2-digit, 1 °C resolution
USABLE INTERNAL VOLUME	109 liters
ELECTRONIC THERMOREGULATION SYSTEM	Traditional
TEMPERATURE REGULATION	$20^{\circ}\text{C}$ constant
INTERNAL TEMPERATURE STABILITY	$\pm 0.5^{\circ}\text{C}$
INTERNAL TEMPERATURE HOMOGENEITY	$\pm 0.5^{\circ}\text{C}$
NUMBER OF SHELVES INCLUDED	2
NUMBER OF INTERNAL SOCKETS	2
POWER	120 W
POWER SUPPLY	230 V / 50-60 Hz
WEIGHT	36 kg (79.4 lb)
DIMENSIONS (WXHxD)	540x912x550 mm (21.3x35.9x21.7 in)



We reserve the right to make technical alterations  
We do not assume liability for errors in printing, typing or transmission

VELP Official Partner

## DESIGNED AND MANUFACTURED IN ITALY



**ITALY - HQ**  
Via Stazione 16  
20865 Usmate (MB) Italy  
Tel. +39 039 628811  
velpitalia@velp.com

**INDIA**  
velpindia@velp.com

**USA**  
155 Keyland Court, Bohemia  
NY 11716 - U.S.  
Tel. +1 631 573 6002  
velpusa@velp.com

**CHINA**  
Xinlong Rd Building 28, Lane 1333  
Shanghai city - China  
Tel. +86 18017557329  
velpchina@velp.com